

AFT Flange Adaptor

AFT Flange Adaptor

Universal fittings is an effective method to connect any rigid pipe material from 40mm to 300mm.

The Universal Adaptor allows plain ended pipe to be connected to a variety of flange specifications.

The range of products give a substantial reduction in customer stock holding due to the wide tolerance range, each fitting being suitable for a comprehensive range of pipe types and sizes.

- Available in a range from 40mm – 600mm (1 ½" to 24").
- Quick and efficient installation without disassembly or loose components
- Suits all common rigid pipe materials
- Universal tolerances that allow for less inventory and so reduce costs
- Prolonged life of fitting due to corrosion protective coating
- Working pressures: Water – up to 16 bar

Every fitting is supplied ready assembled, offering major savings in installation time.

All fittings are supplied ready assembled, allowing for efficient installation on site and all seals are lubricated prior to despatch to aid installation.

The moulded ribs on the seal are designed so that any minor imperfections in the pipe caused by corrosion, pitting or scoring are taken up.
corrosion protection

The epoxy coating offers excellent impact and abrasion resistance. The epoxy coating is applied internal and external and it's non-toxic epoxy coating 200°C hot cycle, std. colours, according to Standards epoxy coating procedures - minimum thickness 250 micron - suitable for potable water.
This durable coating removes the need for further on site protection and gives the fitting and excellent life span.

The screws and nuts are fully hot deep galvanized and plastic end caps are fitted on the bolt threads for additional protection during transit.

Dimensions and illustrations: dimensions are given in millimetres and are approximate in all cases. Illustrations are actual representation of a certain size of each line of products but do not necessarily represent all notice due to the continuing programme of production improvements, the present catalogue has been edited by technical division of the **A.F.T. Advanced Flow Technology® srl** Legnano - Italy.

The **A.F.T. Advanced Flow Technology® srl** reserves the right to make all the modifications to the information here contained that it considers to be necessary for production reasons, without any advanced notification, even in the middle of supplying the materials here illustrated.



AFT Flange Adaptor

06/2012

A.F.T. ADVANCED FLOW TECHNOLOGY® s.r.l. - Via S.Banfi, 3 - 20025 LEGNANO - MI - Italy
Tel: 39+0331+455162 - Fax: 39+0331+486989 - e-mail: Info@aft-advanced.it - Website: www.aft-advanced.it
Azienda Certificata UNI EN ISO 9001-Ed.2008

Universal fittings is an effective method to connect any rigid pipe material from 40mm to 300mm.

The Universal Adaptor allows plain ended pipe to be connected to a variety of flange specifications.

The range of products give a substantial reduction in customer stock holding due to the wide tolerance range, each fitting being suitable for a comprehensive range of pipe types and sizes.

- Available in a range from 40mm — 600mm (1 1/2" to 24").
- Quick and efficient installation without disassembly or loose components
- Suits all common rigid pipe materials
- Universal tolerances that allow for less inventory and so reduce cost
- Prolonged life of fitting due to corrosion protective coating
- Working pressures: Water — up to 16 bar